

Certificate of Compliance

Certificate: 163801-1003088 (LR 102723-1)

Project: 1003088 Date Issued: May 19, 1999

Issued To: BECCA Inc.

'The products listed below are eligible to bear the CSA Mark shown, with adjacent indicator "C" and "US".



Issued by: G. Foulem, E.I.T.

Signature:

PRODUCTS

CLASS 2258 02 - PROCESS CONTROL EQUIPMENT - For Hazardous Locations
CLASS 2258 82 - PROCESS CONTROL EQUIPMENT - For Hazardous Locations - CERTIFIED TO U.S.
STANDARDS

Class I, Division 1, Group D

- Solvent recycler, permanently connected, stationary. Models SRS75XPM and SRS175XPM, rated 240V ac, 1 phase, 60Hz, 3kW, 13.5A, Temp Code T2-300C
- Solvent recycler, permanently connected, stationary. Model SRS550XPM-PC, rated 240V ac, 1 phase, 60Hz, 10kW, 45A, Temp Code T2-300C.

DOD 507WP 99/05/01

The "C" and "US" indicator adjacent to the CSA Mark signifies that the product has been evaluated to the applicable ANSI/UL and CSA Standards, for use in the U.S. and Canada. This includes products eligible to bear the NRTL indicator. NRTL, i.e. Nationally Recognized Testing Laboratory, is a designation granted by the U.S. Occupational Safety and Health Administration (OSHA) to laboratories which have been recognized to perform certification to U.S. Standards.



Certificate No: LR 102723-1 Date: February 8, 1996

Revision: LR 102723-2

Notes:

Final acceptance of installation subject to local inspection authorities having jurisdiction.

2. For use per manufacturer's instruction manual, for mounting clearances, appropriate deposit bag, and conditions of use.

3. For use only with specified solvents as per manufactuer's instruction manual.

APPLICABLE REQUIREMENTS

CAN/CSA-C22.2 No. 14-95 - Industrial Control Equipment
CAN/CSA-C22.2 No. 30-M1986 - Explosion-Proof Enclosures for Use in Class I Hazardous Locations
CAN/CSA-C22.2 No. 88-1958 - Construction and Tests of Industrial Heating Equipment

UL Std No. 508 (16th Ed.) - Industrial Control Equipment

UL Std No. 823 - Electric Heaters for Use in Hazardous (Classified) Locations

UL Std No. 2208 (1st Ed.) - Solvent Distallation Units

DQD 507WP 99/05/01